Model R·SHARK

GREEN POWER

SHARK ROSCAMAT

Reach 1215 mm. -48”
Height 636 mm. -32”

- TAP UP TO M36 – 1 3/8”
- TAP UP TO M27 – 1” in horizontal
- 220 V. Single Phase. Available 110 V.
- High frequency motor
- Electronic speed indicator
- Speed control foward & reverse
- 1 Motor 6 speed capabilities
- 6 interchangeable speed modules
- Tool lubrication with timer
- Tapping depth control
- Heavy duty cast aluminium construction

Ver más del modelo



Orientable Head V-H Lex 90º

OPTIONS

- Vertical tapping
- Vertical & Horizontal tapping -VH- (4x90º)



(90kg./mm2)
M42 (aluminium)

TAP UP TO **M27 1”** in Horizontal

TAP UP TO **M36 1-3/8”**

Description	Orientation	Speed RPM	Capacity Metric	Capacity Inch
ROSCAMAT SHARK	Vertical	40 - 900	M2-M36	#0 – 1 3/8”
ROSCAMAT SHARK VH	Vertical & Horizontal	40 - 900	M2-M36	#0 – 1 3/8”

Single Phase
220 VOLT
Available in 110 V

pises® maquinaria y herramientas



Modular System - Interchangeable Speed

Module	Max. speed. (rpm)	Torque max. Nm	Torque max. Ft•lb	Adapter Size	Tapping Capacity - Steel <90Kg Metric	Tapping Capacity - Steel <90Kg Inches
40	40	340	251	ø 48/3	M27-M36	1/2” – 1 3/8”
75	75	185	136	ø 31/2	M18-M27	5/16” – 7/8”
140	140	95	70	ø 31/2	M18- M22	5/16” – 3/4”
320	320	44	32	ø 19/1	M2-M16	#0 – 9/16”
500	500	28	21	ø 19/1	M2-M12	#0 – 7/16”
900	900	15	11	ø 19/1	M2-M8	#0 – 5/16”

Modules for Model R-SHARK