











## FICHA TÉCNICA

# WIN TIG DC 250 T

[Art. 555]

GENERADOR INVERTER TRIFÁSICO COMPACTO PARA SOLDADURA MMA Y TIG DC CEBADO CON ALTA FRECUENCIA

icons8-electrical-35.png 208/220/230 V 400/440 V  
50/60 Hz  $\pm 10\%$

Art.	555				Datos técnicos
	TIG		MMA		
	208/220/230 V 50/60 Hz $\pm 10\%$	400/440 V 50/60 Hz $\pm 10\%$	208/220/230 V 50/60 Hz $\pm 10\%$	400/440 V 50/60 Hz $\pm 10\%$	Alimentación trifásica Three phase input
	16 A	10 A	16 A	10 A	Fusible de acción retardada Fuse rating (slow blow)
	5,7 kVA 25% 4,0 kVA 60% 2,8 kVA 100%	6,2 kVA 35% 5,0 kVA 60% 4,0 kVA 100%	7,5 kVA 30% 4,9 kVA 60% 3,7 kVA 100%	7,0 kVA 60% 4,5 kVA 100%	Potencia absorbida Input power
	5 ÷ 230 A	5 ÷ 250 A	10 ÷ 210 A	10 ÷ 210 A	Rango de regulación de la corriente Current adjustment range
	230 A 25% 180 A 60% 140 A 100%	250 A 35% 210 A 60% 180 A 100%	210 A 30% 150 A 60% 120 A 100%	140 A 35% 125 A 60% 115 A 100%	Factor de servicio (10 min. 40° C) Según normas IEC 60974-1 Duty Cycle (10 min. 40° C) According to IEC 60974-1
	IP23S				Grado de protección Protection class
	22,7 kg				Peso Weight
	207x437x411 mm				Dimensiones (L x P x H) Dimensions (WxLxH)